

**STATE TRADING CORPORATION**  
**INVITATION TO BID**  
**ACQUISITION OF LAND AND A CENTRAL WAREHOUSING FACILITY ON**  
**DESIGN & BUILD BASIS**

Addendum No.2

This Addendum No.2 dated 18 January 2019 shall form part of the bidding documents for “Acquisition of Land and a Central Warehousing Facility on Design and Build Basis”

1. **Page #11 – Eaves Height**

Delete “Eaves Height to be minimum 6m”

Add “Eaves height below the bottom structural member of the main supporting truss shall be minimum 7m from the ground level.

2. **Page #12 and #13 – Loading Bays/Delivery Bays/Doors**

Delete existing texts

Add following:

◆ **Loading Bays and Doors (Sale to customers)**

- All the loading bays (20 No. minimum) shall be covered with canopies over a width of 6m.
- 14 No. loading bays (minimum) shall be levelled with adjoining roads taking care to provide slope to prevent water from penetrating into warehouse with proper cut-off drains.
- 6 No. loading bays shall be raised at 1150mm above adjacent roads with ramps for the fork lifts. There shall be 4No. raised loading bays for the flour section and 2 No. raised loading bays for the rice section.
- The edges of the above (6 No) loading bays shall be protected with hard timber boards and galvanised angle sections well fixed into the concrete floor slabs
- There shall be heavy duty lockable sliding doors at least 4.0m wide by 4.5m high with automatic closing mechanism and with manual overrides in case of mechanical or electrical failures. These sliding doors shall be located at a maximum distance of 16m apart (centreline to centreline).
- All doors shall be provided with heavy duty vinyl strips

◆ **Delivery Bays and Doors (Receiving from suppliers)**

- At the rear of the warehouse, there shall be delivery bays for offloading of trucks or containers along full length of the proposed warehouse and covered with canopies over a width of 4.0m
- These delivery bays shall be more or less level with adjacent roads with a proper slope between warehouse floors and the adjacent roads
- There shall be heavy duty lockable sliding doors at least 4.0m wide by 4.5m high with automatic closing mechanism and with manual overrides in case of mechanical or electrical failures. These sliding doors shall be located at a maximum distance of 16m apart (centreline to centreline).

- All doors shall be provided with heavy duty vinyl strips

State Trading Corporation

18 January 2019